MATERIAL SAFETY DATA SHEET

DATE OF PREPARATION Jul 11, 2015

SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER B66W310 PRODUCT NAME PRO INDUSTRIAL[™] PRO-CRYL® Universal Acrylic Primer, Off White MANUFACTURER'S NAME THE SHERWIN-WILLIAMS COMPANY 101 Prospect Avenue N.W. Cleveland, OH 44115

Telephone Numbers and Websites

Product Information	(800) 524-5979
	www.sherwin-williams.com
Regulatory Information	(216) 566-2902
	www.paintdocs.com
Medical Emergency	(216) 566-2917
Transportation Emergency*	(800) 424-9300
*for Chemical Emergency C	ONLY (spill, leak, fire, exposure, or
	accident)

SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

% by Weight	CAS Number	Ingredient	Units	Vapor Pressure
3	29911-28-2	1-(2-Butoxymethylethoxy)-propanol		
		ACGIH TLV	Not Available	0.06 mm
		OSHA PEL	Not Available	
13	1317-65-3	Calcium Carbonate		
		ACGIH TLV	10 mg/m3 as Dust	
		OSHA PEL	10 mg/m3 Total Dust	
		OSHA PEL	5 mg/m3 Respirable Fraction	
10	13463-67-7	Titanium Dioxide		
		ACGIH TLV	10 mg/m3 as Dust	
		OSHA PEL	10 mg/m3 Total Dust	
		OSHA PEL	5 mg/m3 Respirable Fraction	

SECTION 3 — HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.

EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE

EYES: Irritation.

SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.

In a confined area vapors in high concentration may cause headache, nausea or dizziness. SIGNS AND SYMPTOMS OF OVEREXPOSURE

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

HMIS Codes		
Health	1*	
Flammability	0	
Reactivity	0	

SECTION 4 — FIRST AID MEASURES

EYES:Flush eyes with large amounts of water for 15 minutes. Get medical attention.SKIN:Wash affected area thoroughly with soap and water.
Remove contaminated clothing and launder before re-use.INHALATION:If affected, remove from exposure. Restore breathing. Keep warm and quiet.

INGESTION: Do not induce vomiting. Get medical attention immediately.

SECTION 5 — FIRE FIGHTING MEASURES

FLASH POINT	LEL	UEL	FLAMMABILITY CLASSIFICATION
Not Applicable	Not	Not	Not Applicable
	Applicable	Applicab	le

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Alcohol Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

SECTION 6 — ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate the area. Remove with inert absorbent.

SECTION 7 — HANDLING AND STORAGE

STORAGE CATEGORY

Not Applicable

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m3 (total dust), 3 mg/m3 (respirable fraction), OSHA PEL 15 mg/m3 (total dust), 5 mg/m3 (respirable fraction).

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

SPECIFIC GRAVITY 1.23 BOILING POINT 212 - 449 °F 100 - 231 °C MELTING POINT Not Available VOLATILE VOLUME 63% EVAPORATION RATE Slower than ether VAPOR DENSITY Heavier than air SOLUBILITY IN WATER Not Available pH > 2.0, < 11.5 VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)			
BOILING POINT 212 - 449 °F 100 - 231 °C MELTING POINT Not Available VOLATILE VOLUME 63% EVAPORATION RATE Slower than ether VAPOR DENSITY Heavier than air SOLUBILITY IN WATER Not Available pH > 2.0, < 11.5 VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)	PRODUCT WEIGHT	10.23 lb/gal	1225 g/l
MELTING POINT Not Available VOLATILE VOLUME 63% EVAPORATION RATE Slower than ether VAPOR DENSITY Heavier than air SOLUBILITY IN WATER Not Available pH > 2.0, < 11.5 VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)	SPECIFIC GRAVITY	1.23	
VOLATILE VOLUME 63% EVAPORATION RATE Slower than ether VAPOR DENSITY Heavier than air SOLUBILITY IN WATER Not Available pH > 2.0, < 11.5 VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)	BOILING POINT	212 - 449 °F	100 - 231 °C
EVAPORATION RATE Slower than ether VAPOR DENSITY Heavier than air SOLUBILITY IN WATER Not Available pH > 2.0, < 11.5 VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)	MELTING POINT	Not Available	
ether VAPOR DENSITY Heavier than air SOLUBILITY IN WATER Not Available pH > 2.0, < 11.5 VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)	VOLATILE VOLUME	63%	
VAPOR DENSITY Heavier than air SOLUBILITY IN WATER Not Available pH > 2.0, < 11.5 VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)	EVAPORATION RATE	Slower than	
SOLUBILITY IN WATER Not Available pH > 2.0, < 11.5 VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)		ether	
pH > 2.0, < 11.5 VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)	VAPOR DENSITY	Heavier than air	
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)	SOLUBILITY IN WATER	Not Available	
· · · · · · · · · · · · · · · · · · ·	pH	> 2.0, < 11.5	
0.90 lb/gal 06 g/L Loss Water and Enderally Exampt Solventa	VOLATILE ORGANIC COMPOUNDS (VOC The	eoretical - As Packa	ged)
	с с с		lerally Exempt Solvents
0.32 lb/gal 39 g/l Emitted VOC	0.32 lb/gal 39 g/l	Emitted VOC	

SECTION 10 — STABILITY AND REACTIVITY

STABILITY — Stable CONDITIONS TO AVOID None known. INCOMPATIBILITY None known. HAZARDOUS DECOMPOSITION PRODUCTS By fire: Carbon Dioxide, Carbon Monoxide HAZARDOUS POLYMERIZATION Will not occur

SECTION 11 — TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

TOXICOLOGY DATA

CAS No.	Ingredient Name			
29911-28-2	1-(2-Butoxymethylethoxy)-propanol			
	LC50 RAT	4HR	Not Available	
	LD50 RAT		Not Available	
1317-65-3	Calcium Carbonate			
	LC50 RAT	4HR	Not Available	
	LD50 RAT		Not Available	
13463-67-7	Titanium Dioxide			
	LC50 RAT	4HR	Not Available	
	LD50 RAT		Not Available	

SECTION 12 — ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

No data available.

SECTION 13 — DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

SECTION 14 — TRANSPORT INFORMATION

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (ocean, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport.

US Ground (DOT) Not Regulated for Transportation. Canada (TDG) Not Regulated for Transportation.

IMO Not Regulated for Transportation.

IMO

Not Regulated for Transportation.

IATA/ICAO

Not Regulated for Transportation.

SECTION 15 — REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No. CHEMICAL/COMPOUND No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

% by WT

% Element

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **TSCA CERTIFICATION**

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

SECTION 16 — OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.