



101.77A

HARMONY[®]

Interior Latex Semi-Gloss B10-1000 Series

As of 05/14/2014, Complies with:		
OTC	Yes	LEED® 09 CI Yes
SCAQMD	Yes	LEED® 09 NC Yes
CARB	Yes	LEED® 09 SC Yes
CARB SCM 2007	Yes	LEED® H Yes
MPI	Yes	NGBS Yes

<u>CHARACTERISTICS</u>	<u>SPECIFICATIONS</u>	<u>SURFACE PREPARATION</u>									
<ul style="list-style-type: none"> Formaldehyde Reducing Technology helps improve indoor air quality by reducing VOCs from possible sources like insulation, carpet, cabinets and fabrics.* Odor Eliminating Technology helps reduce common indoor odors so rooms stay fresher, longer.* Anti-microbial agents inhibit the growth of mold and mildew on the paint surface and inhibit the growth of bacterial odors. Zero VOC formula tinted with ColorCast Ecotoner® Colorants that do not add VOCs when tinted. Great hide and a durable finish that withstands frequent washings. Harmony's Formaldehyde Reducing Technology has been tested by a third-party laboratory. <p>Color: Most Colors To optimize hide and color development, always use the recommended P-Shade primer</p> <p>Coverage: 350-400 sq ft/gal @ 4 mils wet; 1.6 mils dry</p> <p>Drying Time, @ 77°F, 50% RH: Touch: 1 hour Recoat: 4 hours Drying and recoat times are temperature, humidity, and film thickness dependent</p> <p>Flash Point: N/A</p> <p>Finish: 35 - 45 units @ 60°</p> <p>Tinting with CCE only:</p> <table border="1"> <thead> <tr> <th>Base</th> <th>oz/gal</th> <th>Strength</th> </tr> </thead> <tbody> <tr> <td>Extra White</td> <td>0-5</td> <td>125%</td> </tr> <tr> <td>Deep Base</td> <td>4-12</td> <td>100%</td> </tr> </tbody> </table> <p>Vehicle Type: Acrylic Latex Extra White B10W01051</p> <p>VOC (EPA Method 24): <50 g/L; 0.42 lb/gal As per 40 CFR 59.406 and SOR/2009-264, s.12</p> <p>Volume Solids: 42 ± 2%</p> <p>Weight Solids: 54 ± 2%</p> <p>Weight per Gallon: 10.5 lb</p> <p>*The length of time Harmony actively reduces odors and formaldehyde depends on the concentration, the frequency of exposure and the amount of painted surface area.</p>	Base	oz/gal	Strength	Extra White	0-5	125%	Deep Base	4-12	100%	<p>Block 1 ct. Loxon Block Surfer* 2 cts. Harmony Interior Latex</p> <p>Drywall 1 ct. Harmony Interior Latex Primer 2 cts. Harmony Interior Latex</p> <p>Masonry 1 ct. Loxon Concrete & Masonry Primer/Sealer* or Harmony Interior Latex Primer 2 cts. Harmony Interior Latex</p> <p>Plaster 1 ct. Premium Wall & Wood Primer* or Harmony Interior Latex Primer 2 cts. Harmony Interior Latex</p> <p>Wood, Composition Board 1 ct. Premium Wall & Wood Primer* or Harmony Interior Latex Primer 2 cts. Harmony Interior Latex</p> <p>* These primers contain relatively low amounts of VOCs, but could result in minor, noticeable odors.</p> <p>Other primers may be appropriate.</p> <p>When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.</p>	<p>WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p> <p>Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Existing peeled or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull. Stains from water, smoke, ink, pencil, grease, etc. should be sealed with the appropriate primer/sealer.</p> <p>Drywall Fill cracks and holes with patching paste/spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.</p> <p>Masonry, Concrete, Cement, Block All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Concrete & Masonry Primer/Sealer.</p>
Base	oz/gal	Strength									
Extra White	0-5	125%									
Deep Base	4-12	100%									



**SHERWIN
WILLIAMS.**

101.77A

HARMONY®
Interior Latex
Semi-Gloss
B10-1000 Series

<u>SURFACE PREPARATION</u>	<u>APPLICATION</u>	<u>CAUTIONS</u>
<p>Plaster Bare plaster must be cured and hard. Textured, soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with clear water and allow to dry.</p> <p>Wood Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.</p> <p>Mildew Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.</p> <p>Caulking Gaps between walls, ceilings, crown moldings, and other interior trim can be filled with the appropriate caulk after priming the surface.</p>	<p>Apply at temperatures above 50°F. No reduction necessary. Brush—Use a nylon/polyester brush. Roller—Use a 3/8" - 3/4" nap synthetic roller cover. Spray—Airless Pressure..... 2000 psi Tip..... .013"-.017"</p> <p><u>CLEANUP INFORMATION</u> Clean spills, spatters, hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.</p>	<p>For interior use only. Protect from freezing. Non-photochemically reactive.</p> <p><u>LABEL CAUTIONS</u> Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. HOTW 05/14/2014 B10W01051 04 00</p> <p>The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.</p>