



**SHERWIN
WILLIAMS.**

SherLux Harmony Flat

Description	System Recommendation																			
<p>SherLux Harmony Flat is an excellent, durable quality low odor zero voc interior 100 % Acrylic flat paint which is having good, washability hiding, whiteness, luxury finish and leveling properties .Excellent adhesion to the substrate. Anti – Microbial and Anti Bacterial properties. Wide range of vibrant colors.</p>	<p>On old & Porous Substaries:</p> <table border="1"> <tr> <td>SherLux Base Coat</td> <td colspan="2">One coat to fill imperfections</td> </tr> <tr> <td>SherLux Prep Masonry Primer</td> <td colspan="2">One coat</td> </tr> <tr> <td>SherLux Harmony Flat</td> <td colspan="2">Two Coats</td> </tr> </table>			SherLux Base Coat	One coat to fill imperfections		SherLux Prep Masonry Primer	One coat		SherLux Harmony Flat	Two Coats									
SherLux Base Coat	One coat to fill imperfections																			
SherLux Prep Masonry Primer	One coat																			
SherLux Harmony Flat	Two Coats																			
Characteristics	<p>On new cured concrete, plastered and gypsum substrates:</p> <table border="1"> <tr> <td>SherLux Base Coat</td> <td colspan="2">One coat to fill imperfections</td> </tr> <tr> <td>SherLux Prep Masonry Primer</td> <td colspan="2">One coat</td> </tr> <tr> <td>SherLux Harmony Flat</td> <td colspan="2">2 Coats</td> </tr> </table>			SherLux Base Coat	One coat to fill imperfections		SherLux Prep Masonry Primer	One coat		SherLux Harmony Flat	2 Coats									
SherLux Base Coat	One coat to fill imperfections																			
SherLux Prep Masonry Primer	One coat																			
SherLux Harmony Flat	2 Coats																			
<p>Colour As per color card</p> <p>Finish Flat</p> <p>Solid contents (% by volume) 45 ± 2 %</p> <p>Specific Gravity 1.40- 1.50</p> <p>Recommended dry Film Thickness 30 microns</p> <p>Theoretical Coverage: 15 m²/ltr</p> <p>Flash Point: Non flammable</p>	<p>Drying Time: Typically at recommended film thickness , drying time is generally depend on good ventilation.</p>																			
<p>Properties tested as per international Standards</p> <p>Viscosity ASTM D 562</p> <p>Specific Gravity ASTM D 1475</p> <p>Gloss ASTM D 523</p>	<table border="1"> <thead> <tr> <th rowspan="2">Substrate Temp</th> <th rowspan="2">Dry to Touch</th> <th rowspan="2">Dry to Handle</th> <th colspan="2">Re-coating Interval</th> </tr> <tr> <th>Minimum</th> <th>Maximum</th> </tr> </thead> <tbody> <tr> <td>23° C</td> <td>30 mnts</td> <td>3 h</td> <td>2hr</td> <td></td> </tr> <tr> <td>35° C</td> <td>15 mnts</td> <td>2 h</td> <td>1hr</td> <td></td> </tr> </tbody> </table>			Substrate Temp	Dry to Touch	Dry to Handle	Re-coating Interval		Minimum	Maximum	23° C	30 mnts	3 h	2hr		35° C	15 mnts	2 h	1hr	
Substrate Temp	Dry to Touch	Dry to Handle	Re-coating Interval																	
			Minimum	Maximum																
23° C	30 mnts	3 h	2hr																	
35° C	15 mnts	2 h	1hr																	
Packing Size	Storage & Handling																			
<p>1 USG and 18 Liters. Packing may vary from country to country according to local requirements. Also available in bases for instant color mixing at point of sale through Sherwin Williams automatic dispensing system.</p>	<p>Product must be stored in accordance to national regulations. The product should be kept in well ventilated place protected from heat and direct sunlight. The containers must be kept tightly closed.</p>																			



**SHERWIN
WILLIAMS.**

SherLux Harmony Flat

Safety Precautions	Application Procedures
<p>Material health and safety data sheet is available upon request. Please observe the precautionary notice displayed on the container. Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapors and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.</p>	<p><u>Surface Preparation:</u> The surface should be properly primed ..</p> <p><u>Application Conditions:</u> Minimum temperature at 15° C and relative humidity 20 - 85%.</p> <p><u>Application Details:</u> Application method By airless , Brush or roller Thinning Fresh water (only when required) Paint is ready to use Recommended thinning For brush/ roller / Airless max. 5 to 10 %</p> <p><u>Guiding data for airless spray:</u> Nozzle orifice .015 " - .021 " Nozzle Pressure 150 BARS / 2100 psi</p>
Recommended Uses	Environmental Compliance
<p>Can be used on most surfaces i.e. plaster, stucco filler, gypsum board, concrete, asbestos, cement sheeting, rendered block work etc. This product is recommended for interior use only.</p>	<p>VOC Limits Complies to</p> <p>LEED EQ credit 4.2</p> <p>MPI</p> <p>Green Seal GS 11</p> <p>EPA</p> <p>VOC < 0 g/l</p>