



**SHERWIN
WILLIAMS.**

SherLux Interior Texture H.B.

Description	System Recommendation																																																		
<p>SherLux Interior Texture H.B. is an Acrylic based Texture which creates many different patterns of textures when it is applied by hopper gun and trowel.</p>	<p>On old & Porous Substaries:</p> <table border="1"> <tr> <td>SherLast Primer Sealer</td> <td colspan="3"></td> <td>One coat</td> </tr> <tr> <td>SherLux Interior Texture H.B.</td> <td colspan="3"></td> <td>1 Coat</td> </tr> <tr> <td>Any recommended top coat</td> <td colspan="3"></td> <td>2 Coats</td> </tr> </table> <p>On new cured concrete, plastered and gypsum substrates:</p> <table border="1"> <tr> <td>SherLux Primer</td> <td colspan="3"></td> <td>1 coat</td> </tr> <tr> <td>SherLux Interior Texture H.B.</td> <td colspan="3"></td> <td>1 Coat</td> </tr> <tr> <td>Any recommended top coat</td> <td colspan="3"></td> <td>2 Coats</td> </tr> </table> <p>Drying Time: Typically at recommended film thickness , drying time is generally depend on good ventilation.</p> <table border="1"> <thead> <tr> <th rowspan="2">Substrate Temp</th> <th rowspan="2">Dry to Touch</th> <th rowspan="2">Dry to Handle</th> <th colspan="2">Re-coating Interval</th> </tr> <tr> <th>Minimum</th> <th>Maximum</th> </tr> </thead> <tbody> <tr> <td>23° C</td> <td>30 mnts</td> <td>3 h</td> <td>2hr</td> <td></td> </tr> <tr> <td>35° C</td> <td>15 mnts</td> <td>2 h</td> <td>1hr</td> <td></td> </tr> </tbody> </table>				SherLast Primer Sealer				One coat	SherLux Interior Texture H.B.				1 Coat	Any recommended top coat				2 Coats	SherLux Primer				1 coat	SherLux Interior Texture H.B.				1 Coat	Any recommended top coat				2 Coats	Substrate Temp	Dry to Touch	Dry to Handle	Re-coating Interval		Minimum	Maximum	23° C	30 mnts	3 h	2hr		35° C	15 mnts	2 h	1hr	
SherLast Primer Sealer				One coat																																															
SherLux Interior Texture H.B.				1 Coat																																															
Any recommended top coat				2 Coats																																															
SherLux Primer				1 coat																																															
SherLux Interior Texture H.B.				1 Coat																																															
Any recommended top coat				2 Coats																																															
Substrate Temp	Dry to Touch	Dry to Handle	Re-coating Interval																																																
			Minimum	Maximum																																															
23° C	30 mnts	3 h	2hr																																																
35° C	15 mnts	2 h	1hr																																																
Characteristics																																																			
<p>Colour White</p> <p>Finish Flat</p> <p>Solid contents (% by volume) 58 ± 2 %</p> <p>Specific Gravity 1.68- 1.75</p> <p>Recommended dry Film Thickness 300 to 500 microns</p> <p>Theoretical Coverage: 1 m²/kg</p> <p>Flash Point: Non flammable</p> <p>Properties tested as per international Standards</p> <p>Viscosity ASTM D 562</p> <p>Specific Gravity ASTM D 1475</p> <p>Gloss ASTM D 523</p>																																																			
Packing Size	Storage & Handling																																																		
<p>25 kgs. Packing may vary from country to country according to local requirements.</p>	<p>Product must be stored in accordance to national regulations. The product should be kept in well ventilated place protected from heat and direct sunlight. The containers must be kept tightly closed.</p>																																																		



**SHERWIN
WILLIAMS.**

SherLux Interior Texture H.B.

Safety Precautions	Application Procedures				
<p>Material health and safety data sheet is available upon request. Please observe the precautionary notice displayed on the container. Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapors and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.</p>	<p><u>Surface Preparation:</u> The surface should be properly primed . In case of chalky and difficult surfaces it should be primed with SherLast Primer Sealer.</p> <p><u>Application Conditions:</u> Minimum temperature at 15° C and relative humidity 20 - 85%.</p> <p><u>Application Details:</u></p> <table><tr><td>Application method</td><td>Hopper Gun, Scraper.</td></tr><tr><td>Thinning</td><td>Paint is ready to use</td></tr></table>	Application method	Hopper Gun, Scraper.	Thinning	Paint is ready to use
Application method	Hopper Gun, Scraper.				
Thinning	Paint is ready to use				
Recommended Uses	Environmental Compliance				
<p>Can be used on most surfaces i.e. plaster, gypsum board, concrete, asbestos, cement sheeting, rendered block work etc. This product is recommended for interior use only.</p>	<p>VOC Limits Complies to</p> <p>LEED EQ credit 4.2</p> <p>MPI E3</p> <p>Green Seal GS 11</p> <p>EPA</p> <p>VOC < 50g/l</p>				