



Epoxy Reducer/Thinner

Description	System Recommendation								
<p>A special type of compound solvent, which is developed to adjust the flow of Epoxy paints for different types of application methods. It has the ability to thin all types of two component paint Polyurethane paint systems. It can also be tool cleaner.</p>	<p>Please refer to individual product TDS.</p> <p>Drying Time: Typically at recommended film thickness , drying time is generally depend on good ventilation.</p>								
Characteristics									
<table border="0"> <tr> <td>Colour</td> <td>Clear</td> </tr> <tr> <td>Specific Gravity</td> <td>0.87- .89</td> </tr> <tr> <td>Flash Point:</td> <td>39°C</td> </tr> <tr> <td>Specific Gravity</td> <td>ASTM D 1475</td> </tr> </table>	Colour	Clear	Specific Gravity	0.87- .89	Flash Point:	39°C	Specific Gravity	ASTM D 1475	
Colour	Clear								
Specific Gravity	0.87- .89								
Flash Point:	39°C								
Specific Gravity	ASTM D 1475								
Packing Size	Storage & Handling								
<p>1 USG and 5 USG. Packing may vary from country to country according to local requirements. Also available in bases for instant color mixing at point of sale through Sherwin Williams automatic dispensing system</p>	<p>Product must be stored in accordance to national regulations. The product should be kept in well ventilated place protected from heat and direct sunlight. The containers must be kept tightly closed.</p>								



**SHERWIN
WILLIAMS.**

Epoxy Reducer/Thinner

Safety Precautions	Application Procedures
<p>Material health and safety data sheet is available upon request. Please observe the precautionary notice displayed on the container. Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapors and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.</p>	<p><u>Surface Preparation:</u></p> <p>The surface should be made free from moisture if any before application of any paint. Test the surface for moisture-free.</p> <p><u>Application Conditions:</u></p> <p>Minimum temperature at 15° C and relative humidity 20 - 85%.</p>
Recommended Uses	Environmental Compliance
<p>Can be used to thin Epoxy solvent based two component paints.</p>	<p>Lead Free Paint</p>