



SherLast Grip Slip Resistance Additive

Description	Characteristics
<p>SherLast Grip Slip-Resistance Additive is a polymer to be added in Wet Look Sealer for improving the slip resistance. It will mix easily in the latex paint system. It will not have any adverse effect on the coating. It should be added at low agitation.</p>	<p>Melting Point (ASTM D-127) : 320 – 325 F Particle Size : 150 – 170 microns</p>
Characteristics	Caution
<p>Features:</p> <ul style="list-style-type: none"> • Added to latex based and oil based coatings. • Spherical-shaped particles provider a smoother feel and easy to clean surface. • It can be added to paints, stains and sealer. • To be added in low dosage. <p>Benefits:</p> <ul style="list-style-type: none"> • Slip resistance • Easy addition into paints and stains. • Good abrasion and chemical resistance. • Incorporation at slow speed. 	<p>Limitations:</p> <p>SherLast Grip Slip-Resistance Additive is to be considered as a slip resistance and not non-skid. It will increase the coefficient of friction.</p>
Packing Size	Storage & Handling
<p>100 mL and 500 mL.</p>	<p>Product must be stored in accordance to national regulations. The product should be kept in well ventilated place protected from heat and direct sunlight. The containers must be kept tightly closed.</p>
Safety Precautions	<p>Material health and safety data sheet is available upon request. Please observe the precautionary notice displayed on the container. Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapors and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.</p>