



**SHERWIN  
WILLIAMS.**

# Creations Effects Glaze

Description	System Recommendation																	
<p><b>Creation Effects Glaze</b> is a top quality alkyd based specially designed to create verity of special effects such as Color Washing, Sponging, Ragging, Flame, Marble and many other creative finishes.</p>	<p><b>On concrete, plastered and gypsum substrates:</b></p> <table border="1"> <tr> <td>SherLux Primer</td> <td>1 coat</td> </tr> <tr> <td>SherLux Interior Putty</td> <td>1-2 coats</td> </tr> <tr> <td>Sherlux Enamel or Premium Emulsion Semi Gloss</td> <td><b>2 Coats</b></td> </tr> <tr> <td><b>Creation Effects Glaze as per required Technique</b></td> <td><b>1 Coat</b></td> </tr> </table>	SherLux Primer	1 coat	SherLux Interior Putty	1-2 coats	Sherlux Enamel or Premium Emulsion Semi Gloss	<b>2 Coats</b>	<b>Creation Effects Glaze as per required Technique</b>	<b>1 Coat</b>									
SherLux Primer	1 coat																	
SherLux Interior Putty	1-2 coats																	
Sherlux Enamel or Premium Emulsion Semi Gloss	<b>2 Coats</b>																	
<b>Creation Effects Glaze as per required Technique</b>	<b>1 Coat</b>																	
Characteristics	<p><b>Drying Time:</b> Typically at recommended film thickness , drying time is generally depend on good ventilation.</p> <table border="1"> <thead> <tr> <th rowspan="2">Substrate Temp</th> <th rowspan="2">Dry to Touch</th> <th rowspan="2">Dry to Handle</th> <th colspan="2">Re-coating Interval</th> </tr> <tr> <th>Minimum</th> <th>Maximum</th> </tr> </thead> <tbody> <tr> <td>23° C</td> <td>5 hours</td> <td>24 hr</td> <td>4 hr</td> <td></td> </tr> <tr> <td>35° C</td> <td>3.5 hours</td> <td>20 hr</td> <td>3hr</td> <td></td> </tr> </tbody> </table>	Substrate Temp	Dry to Touch	Dry to Handle	Re-coating Interval		Minimum	Maximum	23° C	5 hours	24 hr	4 hr		35° C	3.5 hours	20 hr	3hr	
Substrate Temp	Dry to Touch				Dry to Handle	Re-coating Interval												
		Minimum	Maximum															
23° C	5 hours	24 hr	4 hr															
35° C	3.5 hours	20 hr	3hr															
<p><b>Colour</b> As per color card</p> <p><b>Finish</b> Gloss</p> <p><b>Solid contents (% by volume)</b> 45 ± 2 %</p> <p><b>Specific Gravity</b> 0.9- 1.00</p> <p><b>Recommended dry Film Thickness</b> 20 microns</p> <p><b>Theoretical Coverage:</b> 22.5 m<sup>2</sup>/ltr</p> <p><b>Flash Point:</b> 40°C</p> <p><b>Properties tested as per international Standards</b></p> <p><b>Viscosity</b> ASTM D 4287</p> <p><b>Specific Gravity</b> ASTM D 1475</p> <p><b>Gloss</b> ASTM D 523</p>																		
Packing Size	Storage & Handling																	
<p>1 USG and 18 Liters. Packing may vary from country to country according to local requirements. Also available in bases for instant color mixing at point of sale through Sherwin Williams automatic dispensing system</p>	<p>Product must be stored in accordance to national regulations. The product should be kept in well ventilated place protected from heat and direct sunlight. The containers must be kept tightly closed.</p>																	



**SHERWIN  
WILLIAMS.**

# Creations Effects Glaze

Safety Precautions	Application Procedures				
<p>Material health and safety data sheet is available upon request. Please observe the precautionary notice displayed on the container. Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapors and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.</p>	<p><b><u>Surface Preparation:</u></b> The surface should be properly primed . In case of chalky and difficult surfaces it should be primed with SherLast Primer Sealer.</p> <p><b><u>Application Conditions:</u></b> Minimum temperature at 15° C and relative humidity 20 - 85%.</p> <p><b><u>Application Details:</u></b></p> <table><tr><td>Application method</td><td>Brush, Roller, Rags and Sponge</td></tr><tr><td>Thinning</td><td>Thinner YTF K-099</td></tr></table> <p>Recommended thinning For brush, Roller, Rags and Sponge. max. 20 to 40 %</p>	Application method	Brush, Roller, Rags and Sponge	Thinning	Thinner YTF K-099
Application method	Brush, Roller, Rags and Sponge				
Thinning	Thinner YTF K-099				
Recommended Uses	Environmental Compliance				
<p>Can be used on most surfaces i.e. plaster, stucco filler, gypsum board, concrete, asbestos, cement sheeting, rendered block work etc. This product is recommended for interior use only.</p>	<p><b>Lead Free Paint</b></p>				