



**SHERWIN
WILLIAMS.**

Creations Marble Effect

Description	System Recommendation																			
<p>Creations Marble Effect is a acrylic water based special effect paint which create glossy marble like finish at internal substrates. Can be applied in many techniques to obtain different colored marble finishes.</p>	<p>On old & Porous Substaries:</p> <table border="1"> <tr> <td>SherLast Primer Sealer</td> <td colspan="2">One coat</td> </tr> <tr> <td>SherLux Interior Putty</td> <td colspan="2">1-2 coats to fill imperfections</td> </tr> <tr> <td>SherLux Premium Matt</td> <td colspan="2">2 coats</td> </tr> <tr> <td>Creations Marble Effect</td> <td colspan="2">2 to 3 Coats</td> </tr> </table>			SherLast Primer Sealer	One coat		SherLux Interior Putty	1-2 coats to fill imperfections		SherLux Premium Matt	2 coats		Creations Marble Effect	2 to 3 Coats						
SherLast Primer Sealer	One coat																			
SherLux Interior Putty	1-2 coats to fill imperfections																			
SherLux Premium Matt	2 coats																			
Creations Marble Effect	2 to 3 Coats																			
Characteristics	<p>On new cured concrete, plastered and gypsum substrates:</p> <table border="1"> <tr> <td>SherLux Primer</td> <td colspan="2">1 coat</td> </tr> <tr> <td>SherLux Interior Putty</td> <td colspan="2">1-2 coats to fill imperfections</td> </tr> <tr> <td>SherLux Premium Matt</td> <td colspan="2">2 coats</td> </tr> <tr> <td>Creations Marble Effect</td> <td colspan="2">2 to 3 Coats</td> </tr> </table>			SherLux Primer	1 coat		SherLux Interior Putty	1-2 coats to fill imperfections		SherLux Premium Matt	2 coats		Creations Marble Effect	2 to 3 Coats						
SherLux Primer	1 coat																			
SherLux Interior Putty	1-2 coats to fill imperfections																			
SherLux Premium Matt	2 coats																			
Creations Marble Effect	2 to 3 Coats																			
<p>Colour White</p> <p>Finish Flat</p> <p>Solid contents (% by volume) 53 ± 2 %</p> <p>Specific Gravity 1.65- 1.75</p> <p>Recommended dry Film Thickness 200 microns</p> <p>Theoretical Coverage: 2 m²/kg in one coat</p> <p>Flash Point: Non flammable</p>	<p>Drying Time: Typically at recommended film thickness , drying time is generally depend on good ventilation.</p>																			
<p>Properties tested as per international Standards</p> <p>Viscosity ASTM D 562</p> <p>Specific Gravity ASTM D 1475</p> <p>Gloss ASTM D 523</p>	<table border="1"> <thead> <tr> <th rowspan="2">Substrate Temp</th> <th rowspan="2">Dry to Touch</th> <th rowspan="2">Dry to Handle</th> <th colspan="2">Re-coating Interval</th> </tr> <tr> <th>Minimum</th> <th>Maximum</th> </tr> </thead> <tbody> <tr> <td>23° C</td> <td>2 h</td> <td>3 h</td> <td>2hr</td> <td></td> </tr> <tr> <td>35° C</td> <td>60 mnts</td> <td>2 h</td> <td>1hr</td> <td></td> </tr> </tbody> </table>			Substrate Temp	Dry to Touch	Dry to Handle	Re-coating Interval		Minimum	Maximum	23° C	2 h	3 h	2hr		35° C	60 mnts	2 h	1hr	
Substrate Temp	Dry to Touch	Dry to Handle	Re-coating Interval																	
			Minimum	Maximum																
23° C	2 h	3 h	2hr																	
35° C	60 mnts	2 h	1hr																	
Packing Size	Storage & Handling																			
<p>5 kgs and 14 kgs. Packing may vary from country to country according to local requirements.</p>	<p>Product must be stored in accordance to national regulations. The product should be kept in well ventilated place protected from heat and direct sunlight. The containers must be kept tightly closed.</p>																			



Creations Marble Effect

Safety Precautions	Application Procedures				
<p>Material health and safety data sheet is available upon request. Please observe the precautionary notice displayed on the container. Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapors and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.</p>	<p>Surface Preparation: The surface should be properly primed . In case of chalky and difficult surfaces it should be primed with SherLast Primer Sealer.</p> <p>Application Conditions: Minimum temperature at 15° C and relative humidity 20 - 85%.</p> <p>Application Details:</p> <table border="0"> <tr> <td>Application method</td> <td>Scrapper, Putty Knife</td> </tr> <tr> <td>Thinning</td> <td>Paint is ready to use</td> </tr> </table>	Application method	Scrapper, Putty Knife	Thinning	Paint is ready to use
Application method	Scrapper, Putty Knife				
Thinning	Paint is ready to use				
Recommended Uses	Environmental Compliance				
<p>Can be used on most surfaces i.e. plaster, gypsum board, wood, concrete, asbestos, cement sheeting, rendered block work etc. This product is recommended for interior use only.</p>	<p>VOC Limits Complies to</p> <p>LEED EQ credit 4.2</p> <p>MPI E3</p> <p>Green Seal GS 11</p> <p>EPA</p> <p>VOC < 50g/l</p>				